



IPL-Z44820DS2

8 MP 20X IR Network Speed Dome



■ Features

- 8.0 megapixel HD IP camera, maximum resolution 3840*2160;
- Support POE;
- Support cloud storage;
- Support up to 128G TF card storage;
- 4.7-94mm 20X optical zoom auto focus lens;
- Built-in MIC and speakers, support two way audio;
- Pan tilt rotation, horizontal:355°&vertical:90°;
- Waterproof level IP66;
- 8pcs array infrared LEDs, night vision distance 80m;
- Support P2P, view & anywhere & anytime;
- Elegant outline and easy installation;
- Provide android & ios APP and professional CMS PC client software;





■ Specification

Video	Sensor	8.0 megapixel1/2.8" SONY415Low LuxCMOS
	Video resolution	Main stream:3840*2160@20fps,3072*2048/2592*1944/2560*1440/2304*1296/2048*1536/1080P/960P/720P/D1@30fpsSub stream: 720*480D1/VGA/640*360/CIF@30fps
	Videocompression	H.265/ H.264
	Lens	4.7-94mm 20X optical zoom auto focus lens
	View angle	61.4°~3.6°
	Night vision	8pcsarray infraredLEDs, night visiondistance80m
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input	Built-in MIC and speakers, support two way audio
Alarm	Motion detectingalarm	Can set4independentdetection region(1-100 sensitivitycan be set) alarm mobile phone message push;Alarmsend pictures to the mailbox, Alarmupload pictures and videos to theFTPserver,Alarm recordpictures and videos toMicro SD card,Alarm recordpictures and videos tocloud storageAlarm trigger buzzer alarm, can customizable sound
	Alarm linkage	
Network	Ethernet	RJ45 Ethernet
	Onvifprotocol	Support ONVIF 2.4(backward compatible)
Storage	Micro SD card	Supportup to128Gmicro SD card
	Recording mode	Alarm record, timing record,
	Video playback	Support APP, IE browser, remote clientplay and download the video
	Cloud storage	Support
POE	POE standards	IEEE.802.3af
	Maximum power	12W
	Power conversion	88%
PTZ	Rotation angle	Horizon: 0° ~ 355°,Vertical: 0° ~ 90°
	Horizontal speed	20° ~ 40°/S
	Vertical speed	10° ~ 20°/S
	Preset	Support 8 preset points
General specification	Power	DC12V 2A
	Operatingenvironment	Environment-20°C~+60°C(-4°F~+140°F), Humidity10% ~ 90%, non-condensing
	Waterproof level	IP66
	Products size	190mm×130mm×235mm(L×W×H)
	Productweight	1.4kg
	Package size	275mmx230mmx170mm(L×W×H)
	Package weight	2.0kg

* Product specifications may change without prior notice.





IPL-Z44820DS2

8 MP 20X IR Network Speed Dome

■ Available Model

IPL-Z44520DS2 IPL-Z44820DS2

■ Dimension



■ Accessory

■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

