



UIN-D3708BSF1-A9

8CH/1HDD/H.265 1080N non-real-time DVR





Features

- TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Easily implement network penetration through cloud services and remote monitoring in one step.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- Support VGA, HDMI output at the same time.
- Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.
- Supports more than 20 languages and breaks the limits of national borders.
- Support humanoid functions.
- Support STVI function.
- Support coaxial audio.
- Support Dana Cloud TS Cloud cloud platform customization.





UIN-D3708BSF1-A9

8CH/1HDD/H.265 1080N non-real-time DVR

■ Specification

system	Compression format	H.265
System	operating system	Embedded Linux operating system
video	Input	8
	Preview	8*1080N@25fps
	Coding	8*1080N@15fps
	Decoding	8*1080N@15fps
		0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Channel mode	Support any channel mode combination(1080N analog + 1080P digital)
	VGA output	1080P
	BNC output	Optional, not supported by default
	HDMI output	1080P
Audio	Audio Input	1
	Audio output	1
	Coaxial audio	8
	Two-way intercom	support
Playback	Number of real-timerecording channels	8-way non-real-time
	Video mode	Timing, manual, motion detection
	vides illede	Timing, Tidinaa, Tiolon accessor
	The number of	8
	simultaneousplayback	
	Search mode	Point-in-time search, calendar search, event search, channel search
	USB mobile harddisk, U disk	support
Backup	- , -	''
	USB DVD burner	support
	Format	H.26X、AVI
remote access	Browser	Supports multiple web browsers
	Client	Support VMS
	APP	Support for iPhone, Android
storage	HDD number	1
	E-SATA	not support
Network	Network port	10 / 100 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
other	remote control	support
	power supply	DC12V /2A
	Work Temperature	-10°C ~60°C
	Working humidity	10% ~ 90% Humidity

 $[\]ensuremath{^{*}}$ Product specifications may change without prior notice.





UIN-D3708BSF1-A9

8CH/1HDD/H.265 1080N non-real-time DVR

■ Available Model

UIN-D3708BSF1-A9

■ Rear Panel

■ Dimension



Uin Technology Co., Ltd.

- **486-871 63586112**
- ♠ www.uin-tech.com
- ♀ 4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China