



IPB-D368LDS2(B)

8 MP Dual LED (IR & Color Vu) Fixed Turret Network Camera
Two way audio, Memory Slot



■ Features

- H.265/H.264 8MP IP/Network Dual Light Full Color Turret Camera
- Up to 8 megapixel high resolution
- Max. 3840*2160@20fps(50Hz/60Hz)
- Support RTSP&Onvif(17.2 with profile S)
- Compatible with many third-party NVRs and CMS
- Support multiply Web Browsers: IE/Firefox/Chrome/Safari etc.
- P2P Cloud service
- Free PC Client Software and Smartphone APP(P2P)
- Support Alarm Snapshot to Email and FTP
- Day/Night, AWB/MWB,BLC, 3D-DNR,Shutter, IR-CUT,
- D-WDR,Mirror, Image Flip etc. Functions
- 2.8mm F1.6 fixed lens
- Water-proof: IP66
- 12V DC&PoE
- Built in Mic & Speaker





IPB-D368LDS2(B)

8 MP Dual LED (IR & Color Vu) Fixed Turret Network Camera
Two way audio. Memory Slot

■ Specification

Camera	
Image Sensor:	1/2.7" High sensitivity CMOS
Signal System:	PAL/NTSC
Min. Illumination:	Color: 0.05lux @(F1.6, AGC ON), 0 lux with IR or light
Shutter Time:	1/25 s to 1/10,000 s
Lens:	2.8mm fixed lens
Day&Night:	2pcs Homologous Dual Light (Warm Light+IR LED Light)
Image Enhancement:	BLC/3D DNR
Motion Detection:	Support
Privacy Protection:	Support(4 Self-customized Areas)
Smart function:	Humanoid detection, Vehicle detection
Illumination for Infrared Switching:	0.5~3Lux
Infrared Wavelength:	850nm
Mimimum Illumination:	0 Lux(IR ON)
LED Light Distance	IR 25m/Warm light 20m
Wather-Proof:	IP66
Compression Standard	
Video Compression:	H.265/H.264
Video Bit Rate:	512Kbps~12288Kbps(main stream H.265) 64kbps~1024Kbps(sub stream H.265)
Dual Streams:	Yes
Triple Streams:	No
Image	
Image Resolution:	main stream:3840*2160(8MP)/2596*1944(5MP) /2560*1440(4MP)/1920x1080(1080p) sub stream:720x480(D1)/640x480(VGA)/640x360/352x288(CIF)
Frame Rate:	main stream:20fps(8MP) max. sub stream:30fps max
Stream:	two streams
Image Settings:	3D NR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App
Day/Night mode	support white light mode(full color). Infrared mode (BW with IR led) ,Dual mode(BW with IR led,and white light triggers by Humanoid at night)
Audio	
Audio Compression:	G711U/G711A/AAC
Audio Bitrate	64K(G711)/16k(AAC)
Audio In/Out:	No
Build-in MIC:	Yes
Build-inspeaker:	Yes
Volnume adject:	Yes
Network	
Network Protocols:	Http/Https, TCP/IP, IPv4/v6, UPNP, RTSP/RTMP,FTP, UDP, SMTP, NTP, DHCP, DNS, DDNS,IP Search(Support P2P, NVR, NVS etc.)
General Function:	Anti-Flicker, heartbeat, password protection, privacy mask, Watermark
System Compatibility:	ONVIF(17.2 with profile S)
On-line Viewing	Max. Support 2 Users Simultaneously
Interface	
Communication Interface:	1 RJ45 10M / 100M Ethernet Interface
Audio Interface:	No
Alarm in/out interface:	No
SD card interface	Yes
DC Power Plug:	DC Power Femate Interface/POE
General	
Operating Conditions:	-10 °C ~ 60 °C Humidity 95% or less (non-condensing)
Power Supply:	12 V DC ± 10%/PoE
Power Consumption:	12VDC±10%,Max Power Consumption Less than 8W(When the infrared lamps turn on)
Weight:	0.6KG





IPB-D368LDS2(B)


8 MP Dual LED (IR & Color Vu) Fixed Turret Network Camera
Two way audio, Memory Slot

■ Available Model

IPB-D358LDS2(B) IPY-D368LDS2(B)



■ Dimension

SIZE:mm



■ Accessory

■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

