



WFL-Z44220LDS2

2MP Outdoor Auto Tracking 20X Speed Dome Network Camera with Build-in Mic & Speaker



■ Features

- 2.0 megapixel HD IP camera, maximum resolution 1920x1080;
- High-performance main control chip, good picture quality, support humanoid detection alarm and humanoid tracking;
- Support WIFI or 4G, support AP mode;
- Support up to 128G TF card storage;
- 4.7-94mm 20X optical zoom auto focus lens;
- 8pcs array infrared&white light LEDs, irradiation distance 80m, support color night vision;
- Built-in MIC and speakers, support two way audio;
- Pan tilt rotation, horizontal:355°&vertical:90°;
- Waterproof level IP66;
- Support P2P, view & anywhere & anytime;
- Elegant outline and easy installation;
- Provide android & ios APP and professional CMS PC client software;



**■ Specification**

Video	Sensor	2.0 megapixel 1/2.8" SONY307 Star Light CMOS
	Video resolution	Main stream: 1920x1080@20fps Sub stream: 640x352@25fps
	Video compression	H.265
	Lens	4.7-94mm Zoom 20X optical zoom auto focus lens
	View angle	61.4° - 3.6°
	Night vision	8pcs array infrared&white light LEDs, irradiation distance 80m, support color night vision
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input/output	Built-in MIC and speakers, support two way audio
Alarm	Motion detection	Can set 4 independent detection areas, can set the sensitivity of 1-100
	Humanoid detection	Support, can be used in conjunction with motion detection to make the alarm more accurate
	Alarm linkage	Alarm recording or capture to Micro SD card, Alarm trigger sound alarm, Alarm capture sent to Email, Alarm recording or capture saved to FTP
	Alarm time	All day or manually customize alarm time period
Interface	Power	12V/2A 5.5*2.1mm power interface
	Ethernet	RJ45 Ethernet interface
	Reset button	Support, press for 5 seconds to reset the camera
	Micro SD card	Support up to 128G micro SD card
	Wireless	IEEE 802.11 b/g/n
	Onvif protocol	Support ONVIF 2.4 (backward compatible)
PTZ	Rotation angle	Horizon: 355°, Vertical: 90°
	Horizontal speed	6°-25°/S
	Vertical speed	3°-15°/S
	Preset	Support 8 preset points, cruise function
General specification	Power consumption	Day: 4W, Night: 17W
	Operating environment	Environment -20°C ~ +60°C (-4°F ~ +140°F), Humidity 10% ~ 90%, non-condensing
	Shell material	Metal shell
	Waterproof level	IP66
	Product size	190mm×130mm×235mm(L×W×H)
	Product weight	1.4kg
	Package size	275mm×230mm×180mm(L×W×H)
Package weight	2.0kg	

* Product specifications may change without prior notice.





WFL-Z44220LDS2

2MP Outdoor Auto Tracking 20X Speed Dome Network Camera with Build-in Mic & Speaker

■ Available Model

WFL-Z44220LDS2 (4.7-94mm Zoom 20X)

WFL-Z44520LDS2 (4.7-94mm Zoom 20X)

WFL-Z44820LDS2 (4.7-94mm Zoom 20X)

■ Dimension



■ Accessory

■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

